

BOGE Typ	Höchst- druck		Effektive Liefermenge*		Motor- leistung		Maße schallgedämmt		Maße superschallgedämmt/ mit Radiallüfter		Druck- luft- aus- tritt	Gewicht schallged./ m. Radiallüfter		Gewicht super- schallged. kg
	bar	psig	m³/min	cfm	kW	PS	B x T x H in mm		B x T x H in mm			kg		
SLF 30	8	115	1,06- 3,87	37- 137	22	30	1830 x 966 x 1444	1830 x 966 x 1444	1830 x 966 x 1944	1830 x 966 x 1944	G 1 1/4	700/730	730	
	10	150	1,06- 3,30	37- 117	22	30	1830 x 966 x 1444	1830 x 966 x 1444	1830 x 966 x 1944	1830 x 966 x 1944	G 1 1/4	700/730	730	
	13	190	1,06- 2,68	37- 95	22	30	1830 x 966 x 1444	1830 x 966 x 1444	1830 x 966 x 1944	1830 x 966 x 1944	G 1 1/4	700/730	730	
SLF 40	8	115	1,06- 5,05	37- 178	30	40	1830 x 966 x 1444	1830 x 966 x 1444	1830 x 966 x 1944	1830 x 966 x 1944	G 1 1/4	770/805	810	
	10	150	1,06- 4,53	37- 160	30	40	1830 x 966 x 1444	1830 x 966 x 1444	1830 x 966 x 1944	1830 x 966 x 1944	G 1 1/4	770/805	810	
	13	190	1,06- 3,82	37- 135	30	40	1830 x 966 x 1444	1830 x 966 x 1444	1830 x 966 x 1944	1830 x 966 x 1944	G 1 1/4	770/805	810	
SLF 51	8	115	1,51- 6,71	53- 237	37	50	2040 x 1090 x 1450	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	2040 x 1090 x 1950/2060	G 1 1/4	1020/1070	1070	
	10	150	1,47- 6,04	52- 213	37	50	2040 x 1090 x 1450	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	2040 x 1090 x 1950/2060	G 1 1/4	1020/1070	1070	
	13	190	1,37- 4,98	48- 176	37	50	2040 x 1090 x 1450	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	2040 x 1090 x 1950/2060	G 1 1/4	1020/1070	1070	
SLF 61	8	115	1,55- 7,87	55- 278	45	60	2040 x 1090 x 1450	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	2040 x 1090 x 1950/2060	G 1 1/2	1150/1200	1200	
	10	150	1,51- 6,92	53- 244	45	60	2040 x 1090 x 1450	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	2040 x 1090 x 1950/2060	G 1 1/2	1150/1200	1200	
	13	190	1,42- 5,90	50- 208	45	60	2040 x 1090 x 1450	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	2040 x 1090 x 1950/2060	G 1 1/2	1150/1200	1200	
SLF 75	8	115	1,55- 9,33	55- 329	55	75	2040 x 1090 x 1450	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	2040 x 1090 x 1950/2060	G 1 1/2	1270/1320	1320	
	10	150	1,51- 8,40	53- 297	55	75	2040 x 1090 x 1450	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	2040 x 1090 x 1950/2060	G 1 1/2	1270/1320	1320	
	13	190	1,46- 7,26	52- 256	55	75	2040 x 1090 x 1450	2040 x 1090 x 1450	2040 x 1090 x 1950/2060	2040 x 1090 x 1950/2060	G 1 1/2	1270/1320	1320	
SLF 101	8	115	4,22-13,64	149- 482	75	100	2415 x 1335 x 1750	2415 x 1335 x 1750	2415 x 1335 x 2250	2415 x 1335 x 2250	G 2 1/2	2200/ –	2260	
	10	150	4,16-12,33	147- 435	75	100	2415 x 1335 x 1750	2415 x 1335 x 1750	2415 x 1335 x 2250	2415 x 1335 x 2250	G 2 1/2	2200/ –	2260	
	13	190	4,00-10,58	141- 374	75	100	2415 x 1335 x 1750	2415 x 1335 x 1750	2415 x 1335 x 2250	2415 x 1335 x 2250	G 2 1/2	2200/ –	2260	
SLF 125	8	115	4,22-15,70	149- 554	90	125	2415 x 1335 x 1750	2415 x 1335 x 1750	2415 x 1335 x 2250	2415 x 1335 x 2250	G 2 1/2	2250/ –	2310	
	10	150	4,16-14,36	147- 507	90	125	2415 x 1335 x 1750	2415 x 1335 x 1750	2415 x 1335 x 2250	2415 x 1335 x 2250	G 2 1/2	2250/ –	2310	
	13	190	4,00-12,56	141- 443	90	125	2415 x 1335 x 1750	2415 x 1335 x 1750	2415 x 1335 x 2250	2415 x 1335 x 2250	G 2 1/2	2250/ –	2310	
SLF 221	8	115	6,46-28,21	228- 996	160	220	3145 x 1910 x 2145	3145 x 1910 x 2145	3145 x 1910 x 2645	3145 x 1910 x 2645	DN 100	4500/ –	4600	
	10	150	6,18-25,06	218- 885	160	220	3145 x 1910 x 2145	3145 x 1910 x 2145	3145 x 1910 x 2645	3145 x 1910 x 2645	DN 100	4500/ –	4600	
	13	190	5,46-20,36	193- 719	160	220	3145 x 1910 x 2145	3145 x 1910 x 2145	3145 x 1910 x 2645	3145 x 1910 x 2645	DN 100	4500/ –	4600	
SLF 271	8	115	6,46-34,70	228-1225	200	270	3145 x 1910 x 2145	3145 x 1910 x 2145	3145 x 1910 x 2645	3145 x 1910 x 2645	DN 100	4700/ –	4800	
	10	150	6,18-30,50	218-1077	200	270	3145 x 1910 x 2145	3145 x 1910 x 2145	3145 x 1910 x 2645	3145 x 1910 x 2645	DN 100	4700/ –	4800	
	13	190	5,46-24,73	193- 873	200	270	3145 x 1910 x 2145	3145 x 1910 x 2145	3145 x 1910 x 2645	3145 x 1910 x 2645	DN 100	4700/ –	4800	